

Technical data

VPC 2800 U

VPC 2800 U

Working area

X-traverse range vertical	[mm]	3900
X-traverse range horizontal	[mm]	3900
Y-traverse range	[mm]	2940
Z-traverse range	[mm]	1100

CNC-rotary table

Clamping surface	[mm]	∅ 2800
Max. transport weight	[kg]	15000
Max. tangential moment	[Nm]	40000
Max. tilting moment	[Nm]	90000
Accuracy measuring system	[arcsec]	± 2,5"
Min. distance table - spindle nozzle vert.	[mm]	90
Min. distance table - spindle nozzle hor.	[mm]	180

Feed drive

Max. rapid traverse in X/Y/Z	[m/min]	30/30/25
Max. feed force	[N]	9000

Main spindle drive

Standard drive no. ¹		140
---------------------------------	--	-----

Tool holding fixture

DIN 69871 A / DIN 69872 A		SK 50
Optional		BT 50, HSK A100

Tilting spindle head

Swivelling range B-axis		90°
Indexing		fully interpolating

Tool changer

Number of tool pockets standard		20
Optional expandable up to		120
Max. tool diameter	[mm]	110
By free adjacent pockets	[mm]	180
Max. tool length	[mm]	400 (300) ⁴

Accuracy

Positioning accuracy ²	[mm]	± 0,015 (± 0,008) ²
Repeating accuracy	[mm]	± 0,01 (± 0,006) ²

¹ Main spindle drives

140

Speed range	[rpm]	6000
Optional up to	[rpm]	9000
Max. torque (100% DC)	[Nm]	200
Max. power (100% DC)	[kW]	63

² Optional features

³ Per 1000 mm per axis X/Y/Z with vertical spindle

⁴ Max. tool length 2nd magazine

Technical specifications refer to the standard version.
Extensions and modifications upon request and
depending on overall configuration and application.