

Model VCC 50

Construction year 2016



Technical data

No. 272 – VCC 50	
CNC-System	Siemens 840 Dsl
Traverse ranges X/Y/Z	1350 / 700 / 850 [mm]
Power rapid traverse X/Y/Z	40 / 40 / 30 [m/min]
Clamping surface approx.	1500 x 750 mm
Rotary table	4th axis AXA RTA 3-400
Speed range	30 - 6000 [rpm]
Main drive	max. 57 [kW] (with 40% DC)
Spindle torque	540 [Nm] (with 40% DC)
Spindle taper	SK 50, DIN ISO7388-1 (DIN 69871 A)
Tool changing system	Disc type magazine with 22 tool places
External cooling	Ring with 6 adjustable cooling nozzles
Through spindle coolant	up to 30 bar, incl. belt filter system with external container 400 l
Chip conveyor	Discharge right side, discharge height approx. 1200 mm
Covering	Working space encapsulation
Colour	light grey / slate grey (RAL 7035 / 7015)
Additional features	<ul style="list-style-type: none"> • recooling system for spindle and switchgear cabinet • hydraulically clamped counterbearing, size 50 • operating mode 3 without enabling button • one hand operating flushing gun • two fluorescent tubes

For more information please contact
Herr J. Roters, phone. +49 2555 87-80
verkauf@axa-maschinenbau.de